

M55



DECT



Shared Call Emulation (SCE)



Bluetooth



Anti-bacterial housing



Backlit keypad



Long standby time



Directory



OTA Updates



Belt clip

M55 - Snom's DECT business all-rounder

Designed for scalable SMB environments, the M55 impresses with a robust design and feel. The generous 2.4" color display ensures a clear, well-arranged representation of the intuitive user interface. All settings can be made centrally via the M500 base station using zero-touch provisioning, software updates are done over-the-air. Proven PBX features such as line monitoring, call pickup,

hold/retrieve can be programmed very efficiently on the 6 LED line and function keys. Broadcast and intercom groups can also be saved at the push of a button. The powerful 1500 mAh battery allows up to 12 hours of talk time in HD audio quality. In addition to wired headphones, Bluetooth headphones are also supported.

Product variants



M55 | EU | PN 00004629



M55 | UK | PN 00004630

Basics

- Product information
 - DECT handset
 - Colour: black
 - Anti-bacterial housing
- Placement: indoor, desktop

Dimensions and weight

- Dimensions (L x W x D, approx.)
 - 188 mm x 55 mm x 35 mm
- Weight (approx.)
 - Handset & Battery & belt clip: 188 g

Display and indicators

- Display
 - TFT liquid crystal display (LCD), highcolour, backlit
 - Size (diagonal): 2.4" (61 mm)
 - Resolution: 240 x 320 pixel
- 9 LED indicators
 - Notification of missed calls | Message waiting indication (MWI): 1 red LED
 - Function key status indication: 6 dual-colour LEDs (red / green)
 - Audio key status indication: 1 red LED
 - Charging indication: 1 red LED (on the charging cradle)

Keypad and function keys

- 31 hard keys in total
- 12 keys (standard ITU telephone keypad), backlit
- 5-way navigation key
- 3 context-sensitive function keys
- 6 programmable function keys (with dual-colour LED)
- 3 dedicated audio keys
 - Speakerphone (with red LED), Volume + / - (rocker)
- 2 dedicated function keys
 - Offhook, PFK page
- Keyboard lock

Interfaces and connections

- M55 power options
 - Handset
 - Battery 3.7 V, 1,500 mAh, 5.55 W, lithium-ion, rechargeable, up to 240 h standby time, up to 19 h narrowband talk time, up to 12 h wideband talk time
 - Charging cradle
 - Power adapter: 100 - 240 V AC / 50 - 60 Hz / 300 mA | 5 V DC / 2 A
 - USB powering via USB-A port/cable
- Wired interfaces
 - Headset: 3.5 mm miniature audio jack
- Wireless interfaces
 - DECT
 - Headset (Bluetooth): [Bluetooth](#)

Audio features

- Handset
 - Hearing aid compatible (HAC)
- Speakerphone mode
- Headset connectivity

User interfaces and setup

- Configuration and setup via menu-driven phone user interface (PUI)
 - Languages: English, French, Italian, Spanish, German, Dutch, Greek, Russian
- Localization
 - Timezone, dial tone

Directory support and call features

- Directory support
 - Local directory with up to 200 entries
 - LDAP (server-based directory)¹
 - Central directory on the base station with up to 500 shared entries¹
 - XML phonebook support¹
- Outgoing call features
 - Speed dialling
 - Redial (via dialed calls list)
 - Caller identification (CLIP)
 - Intercom¹
 - Paging¹
- Incoming call features
 - Call waiting/swapping
 - Auto answer
 - Call diversion
- Connected call features
 - Hold
 - Blind call transfer

- Attended call transfer
- 2+1 local conferencing
- Call barging¹
- Call park / unpark¹
- Related features
 - Call history lists
 - Shared Call Emulation²
 - Extension monitoring (Busy lamp field), call pickup¹
 - Paging zones¹
 - Intercom groups¹

DECT technology and features

- Standard: DECT
 - Authentication/encryption of base and handset
 - Seamless handover
 - Wideband audio
- Frequency band: 1,880 - 1,900 MHz
- Output power: < 250 mW
- Coverage
 - Up to 50 m indoor range
 - Up to 300 m outdoor range
- Related features
 - Software upgrade over the air (SUOTA)
 - Auto registration when not registered
 - Date and time synchronization from base station

Network technologies

- Bluetooth
 - Headset Profile (HSP)
 - Wireless range (approx.): 10 m

Environmental conditions

- Operating ambient temperature: 0 °C - 40 °C

Package contents

- Hardware
 - DECT handset M55
 - Battery
 - Charging cradle
 - Power adapter
- Documentation
 - Quick Installation Guide (QIG)

Snom accessories and compatible devices

- Base stations
 - M500 (PN 00004628)
- Power adapter
 - EU: M55 PSU (PN 00004635)
 - UK: M55 PSU (PN 00004636)