



The bridge to possible

[Data sheet](#)  
Cisco public

# Cisco IP Phone 8851/61 Key Expansion Module

---

# Contents

|                                    |   |
|------------------------------------|---|
| Product overview                   | 3 |
| Features and benefits              | 4 |
| Product specifications             | 5 |
| System requirements                | 5 |
| Power requirements                 | 6 |
| Warranty                           | 7 |
| Ordering information               | 6 |
| Cisco environmental sustainability | 7 |
| Cisco Capital                      | 8 |
| For more information               | 8 |

Quickly adapt to market changes. Increase productivity. Improve competitive advantage through speed and innovation. And deliver a rich-media experience across any workspace securely and with the best possible quality. Cisco® Unified Communications Solutions enable the collaboration that makes this possible (Figure 1).



**Figure 1.**  
Cisco IP Phone 8851/61 Key Expansion Module

## Product overview

Call coverage is critical for administrative assistants and others who must monitor and manage the status of calls. It requires the ability to instantly determine the status of numerous lines beyond those of the Cisco IP Phone 8851, 8851NR, and 8861 models.

**Note:** The Cisco IP Phone 8851 and 8861 models includes the standard 8851 model and the 8851NR model, which is the nonradio 8851 and 8865 models. The NR models are designed for military and other customers who need a Key Expansion Module (KEM) but cannot place phones with Bluetooth or other radios on their premises. All attributes of the 8851 and 8851NR are identical except that the 8851NR has no Bluetooth radio on its boards.

The Cisco IP Phone 8851/61 Key Expansion Module extends the capabilities of Cisco IP Phone 8851, 8851NR, and 8861 models with additional buttons and a color LCD display. This key expansion module adds 14 physical keys with access to 14 additional keys, using the page keys, for a total of 28 additional keys. You can connect up to three 8851/61 Key Expansion Modules to the IP Phone 8861 and up to two 8851/61 KEMs to the IP Phone 8851 and 8851NR.

The 8851/61 Key Expansion Module comes with a foot stand and all necessary hardware to connect it directly to the base device in the traditional side-by-side fashion.

## Features and benefits

The large LCD displays of the Cisco IP Phone 8851/61 Key Expansion Module allows for quick and easy identification of associated buttons. Using the settings menu of the IP Phone 8851, 8851NR, and 8861 models, you can adjust the brightness of the individual KEM LCD according to your preference.

The primary function of the 8851/61 Key Expansion Module is to provide additional keys for directory numbers, speed dial, or programmable feature keys to the IP Phone 8851, 8851NR, and 8861 models. These keys are illuminated, and when configured as directory numbers or shared-line keys they allow for easy identification of line status. The 8851/61 Key Expansion Module is an ideal call-coverage tool. It provides features that are similar, but not intended to be directly comparable to those of traditional Direct Station Selection/Busy Lamp Field (DSS/BLF) modules; therefore, it is neither an operator nor an attendant console.

The two illuminated page buttons below the Cisco IP Phone 8851/61 Key Expansion Module display allow you to shift between the first and second page of 14 buttons, providing access to all 28 keys.

Table 1 describes the features and benefits in more detail.

**Table 1.** Features and benefits

| Feature                                   | Benefits   |
|---|--|
| <b>Illuminated Buttons</b>                |  |
| Off (dark)                                | Line available   |
| Green, steady                             | Line in use  |
| Red, steady                               | Line in use by shared line   |
| Amber, flashing                           | Line ringing   |
| <b>Illuminated Page Buttons</b>           |  |
| Off (dark)                                | Page not in focus  |
| Green, steady                             | Page in focus  |
| Amber, flashing                           | Page not in focus, with one or more alerting or on-hold calls present on page  |
| <b>Hardware and Power-Saving Features</b> |  |
| Graphical display                         | The 3.5-inch graphical (TFT) color displays provides 16-bit color depth and 320 x 480 effective pixel resolution, with backlight. The display also supports localization requiring double-byte Unicode encoding for fonts. |
| Articulation                              | You can articulate the display to match the same angle as the Cisco IP Phone 8851, 8851NR, and 8861 that it is connected to.   |
| Directory-number and feature buttons      | The module has 14 physical buttons (28 using page keys).   |

| Feature                  | Benefits  |
|--------------------------|---|
| Page buttons             | Use the two page buttons to access each page of 14 buttons and provide phone status.  |
| Sleep or inactivity mode | When Cisco IP Phone 8851, 8851NR, and 8861 models are in power-saving sleep or inactivity mode, the Cisco IP Phone 8800 KEM is also in sleep or inactivity mode. Pressing any button on the key expansion module causes the display to awaken. The system administrator configures the inactivity period. |

## Product specifications

Table 2 describes the hardware product specifications of the Cisco IP Phone 8851/61 Key Expansion Module.

**Table 2.** Product specifications

| Feature                         | Specifications  |
|---------------------------------|---|
| Physical dimensions (H x W x D) | 9.015 x 4.45 x 1.58 in. (L X W X D)<br>(229 x 113 x 40 mm)  |
| Weight                          | 1lb (448g)  |
| Power                           | 48 VDC, 117 mA maximum  |
| Operating temperature           | 32 to 104° F (0 to 40° C)   |
| Relative humidity               | 10 to 95%   |
| Storage temperature             | 12 to 140° F (-10 to 60° C)   |
| Approvals and compliance        | <a href="https://www.cisco.com/en/US/docs/voice_ip_comm/cuipph/all_models/regulatory_compliance/english/install/guide/iphrcsi3.html">https://www.cisco.com/en/US/docs/voice_ip_comm/cuipph/all_models/regulatory_compliance/english/install/guide/iphrcsi3.html</a> |

## System requirements

Table 3 lists the system requirements for the 8851/61 KEM.

**Table 3.** System requirements

| Phone Firmware/Call Control Server | Release  |
|------------------------------------|--|
| Cisco IP Phone 8800 firmware       | 12.0.1.11 and later  |
| Call-control compatibility         | Cisco Unified Communications Manager Version 10.5(2) and later; and Cisco Unified Survivable Remote Site Telephony (SRST) 11.0 (with Cisco IOS® Software Release 15.3(3)M) and later |

## Power requirements

The Cisco IP Phone 8851/61 Key Expansion Module doesn't have its own local power supply; it gets power from the attached phones. For more power-supply details, please refer to Table 4.

**Table 4.** Power-Supply Compatibility Table

| Configuration  | 802.3af Power over Ethernet (PoE) | 802.3at PoE       | Cisco IP Phone Power Cube 4 |
|----------------|-----------------------------------|-------------------|-----------------------------|
| 8851 + KEM x 1 | Yes                               | Yes               | Yes                         |
| 8851 + KEM x 2 | No                                | No                | Yes                         |
| 8861 + KEM x 1 | No                                | Yes               | Yes                         |
| 8861 + KEM x 2 | No                                | Yes <sup>*</sup>  | Yes                         |
| 8861 + KEM x 3 | No                                | Yes <sup>*</sup>  | Yes                         |
| 8865 + KEM x 1 | No                                | Yes               | Yes                         |
| 8865 + KEM x 2 | No                                | Yes <sup>**</sup> | Yes                         |
| 8865 + KEM x 3 | No                                | Yes <sup>**</sup> | Yes                         |

<sup>\*</sup> **Note:** The fast-charging feature on the back USB does not work when **more than one** KEM is attached to a Cisco IP Phone 8861 using 802.3at PoE.

<sup>\*\*</sup> **Note:** The fast-charging feature on the back USB doesn't work when **more than one** KEM is attached to a Cisco IP Phone 8865 unless Cisco Universal PoE (UPoE) is used.

## Ordering information

To place an order, visit the Cisco Ordering Home Page and refer to Tables 5 and 6.

**Table 5.** Ordering information

| Product Name   | Part Number        |
|--|--------------------|
| Cisco IP Phone 8800 Key Expansion Module                       | CP-8800-A-KEM=     |
| Cisco Unified IP Phone Power Cube 4                            | CP-PWR-CUBE-4=     |
| Cisco Unified IP Phone Power Country Cord                      | CP-PWR-CORD-xx=    |
| Cisco IP Phone 8800 Wall Mount Kit for Single KEM <sup>*</sup> | CP-8800-A-KEM-WMK= |

<sup>\*</sup> **Note:** The Cisco IP Phone Wall-Mount Kit for a single KEM is a locking wall-mount kit that supports the 8851 and 8861 audio phones only. This wall-mount kit does not support the 8865 video phone and a KEM because of the difference in the rear housing on the 8865.

**Table 6.** Ordering information - AC Country Power Cords

| Country Cord       | Part Number     |
|--------------------|-----------------|
| Asia Pacific       | CP-PWR-CORD-AP= |
| Argentina          | CP-PWR-CORD-AR= |
| Australia          | CP-PWR-CORD-AU= |
| European Community | CP-PWR-CORD-CE= |
| China              | CP-PWR-CORD-CN= |
| Japan              | CP-PWR-CORD-JP= |
| North America      | CP-PWR-CORD-NA= |
| Switzerland        | CP-PWR-CORD-SW= |
| United Kingdom     | CP-PWR-CORD-UK= |

## Warranty

Cisco Unified IP Phones are covered by a Cisco standard 1-year replacement warranty.

## Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

| Sustainability topic   | Reference                       |
|--|---------------------------------|
| Information on product material content laws and regulations                                       | <a href="#">Materials</a>       |
| Information on electronic waste laws and regulations, including products, batteries, and packaging | <a href="#">WEEE compliance</a> |

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

---

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments.

[Learn more.](#)

### For more information

For more information about the Cisco IP Phone 8851/61 Key Expansion Module, please visit <https://www.cisco.com/go/ipphones/8800>, or contact your local Cisco account representative.

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)