



# Fanvil i60K SIP Door Phone

## Description

Fanvil i60K is a SIP door phone with a speed dial button, a numeric keypad, and an IP65 rating for indoor and outdoor use. It supports various door-opening methods such as password, Bluetooth, IC/ID card, and DTMF Code for streamlined access management and is equipped with a 2 mega-pixel camera for audio and video communication. Compatible with SIP and ONVIF, it integrates with security systems and is ideal for villas, apartments, and communities.

## Main Features



1 speed-dial button and a numeric keypad



Equipped with a 2 mega-pixel HDR high-definition camera, it provides clearer imaging



IP65 high protection rating with wide temperature rate from -40°C to 70°C, suitable for harsh outdoor environments



Rich interfaces for security device connectivity



Support the standard ONVIF protocol, providing high flexibility and excellent compatibility



## Specifications

|                                |  |
|--------------------------------|--|
| <b>Panel Type</b>              | Multi-apartment, Community, Villa        |
| <b>Keyboard</b>                | 1 speed-dial button and a numeric keypad |
| <b>Body</b>                    | ABS+PC                                   |
| <b>Colors</b>                  | Panel: black, Housing: Gunmetal          |
| <b>Sensor</b>                  | 1/2.9-inch, CMOS                         |
| <b>Camera</b>                  | 2 Mpx, Support infrared                  |
| <b>Viewing Angle</b>           | 140°(FOV) 100°(Horizontal) 57°(Vertical) |
| <b>Output video</b>            | H.264 (Baseline, Main Profile)           |
| <b>Light Sensitivity</b>       | 0.1Lux                                   |
| <b>Card Storage</b>            | 1,0000                                   |
| <b>Power Consumption</b>       | PoE:1.63~6.93W<br>Adapter: 1.51~6.16W    |
| <b>Power Supply</b>            | DC 12V / 1A<br>PoE 802.3af Class 3       |
| <b>Working Temperature</b>     | -40°C~+70°C                              |
| <b>Storage temperature</b>     | -40°C~+70°C                              |
| <b>Size of the Panel (LWH)</b> | 70.7*149.7*30mm                          |
| <b>IP / IK Level</b>           | IP65                                     |
| <b>Installation</b>            | Wall-mounted<br>Rain cover               |

## Functional Capabilities

|                              |   |
|------------------------------|---|
| <b>Supported Protocols</b>   | SIP 2.0 over UDP/TCP/TLS  |
| <b>Lock Opening</b>          | IC Card, By DTMF Code, Remote Door Opening, Password, BLE         |
| <b>Interface</b>             | Wiegand Input/Output<br>Short Circuit Input/Output                |
| <b>Supported Wiegand</b>     | 26, 34 bit  |
| <b>Supported ONVIF Types</b> | Profile S   |
| <b>Supported Standards</b>   | DTMF, IC Card, Indoor Switch, BLE<br>Cards 13.56 MHz              |
| <b>Talking Mode</b>          | Full duplex (High-definition Audio)                               |
| <b>Additionally</b>          | Built-in relay, Motion detection, Tamper Alarm, TF Card, Open API |